

**DECLARATION OF PERFORMANCE**  
**No. 01/2016/ND**

1. Unique identification code of the product - type: **90**
2. Intended use or uses:
  - 2.1. Flexible sheets for waterproofing – Underlays for discontinuous roofing according to EN 13859-1: 2010
    - 2.1.1. As a precoat, sealing roof coverings which are based on battens and counter-battens (MWK) in non-ventilated roofs with ventilated covering with a slope > 20°.
    - 2.1.2. As a protective-spacer layer of thermal insulation under coverings based on sheathings in ventilated roofs with a slope > 15°.
    - 2.1.3. As a sealing of plates of „on-rafter” thermal insulation, e.g. PIR, PUR etc. according to manufacturer’s instructions.
  - 2.2. Flexible sheets for waterproofing – Underlays for walls according to EN 13859-2: 2010
    - 2.2.1. As a sealing and protection of thermal insulation in wooden and concrete ceilings.
3. Manufacturer:
 

Info-GLOBAL sp. j.  
ul. Długa 67  
63-400 Ostrów Wielkopolski  
tel. +48 62 737 27 60 fax. +48 62 737 27 61  
Production plant: ul. Szybowskiego 1, 39-460 Nowa Dęba
4. System of assessment and verification of constancy of performance:
 

Conformity assessment system 3.
5. Harmonized standard:
 

EN 13859-1: 2010 Flexible sheets for waterproofing. Definitions and characteristics of underlays. Part 1: Underlays for discontinuous roofing.

EN 13859-2: 2010 Flexible sheets for waterproofing. Definitions and characteristics of underlays. Part 2: Underlays for walls.

Notified body or bodies:  
Polskie Centrum Badań i Certyfikacji S.A. Oddział Badań i Certyfikacji w Gdańsku Laboratorium Wyrobów Budowlanych, ul. Wejhera 18a, 80-346 Gdańsk, nr 1434.
6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E-d2	EN 13859-1: 2010 EN 13859-2: 2010
Water tightness	W1	
Tensile properties: - along - across	200 +/- 60 [N/50 mm] 120 +/- 60 [N/50 mm]	
Elongation: -along -across	70 +/- 40 [%] 90 +/- 40 [%]	
Water vapour transmission – Sd parameter, i.e. diffusively equivalent air layer thickness	0,015 + 0,02/ - 0,01 [m]	
Resistance to tearing: - along - across	90 +/- 50 [N] 120 +/- 50 [N]	
Flexibility at low temperature	- 25 [°C]	

Resistance to artificial ageing:		
Tensile properties:		
- along	180 +/- 50 [N/50 mm]	
- across	100 +/- 50 [N/50 mm]	
Elongation:		
-along	40 + 40/- 30 [%]	
- across	60 + 40/- 30 [%]	
Water tightness	W1	

The performance of the product identified above are in conformity with the set of declared performances. This declaration of performance is issued according to the regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer indicated above.

The copy of declaration of performance can be found on the manufacturer's website:

[www.himalayanroof.pl](http://www.himalayanroof.pl)

Signed on behalf of the manufacturer by:



Szymon Jaś, Product Manager  
Ostrów Wielkopolski, 20.05.2016